



**AHTS**

# Vessel specs

Built / Yard	2008
Design	UT 712 L
Flag	NOR
LOA	78.3m
Breadth Moulded	17.2m
Yard	Aker Brevik AS
Main Class	+1A1, SF, E0, DK(+), HL(2,5), TUG, SUPPLY VESSELS, CLEAN, DYNPOS-AUTR, FiFi I, TMON
Classification Society	DNV GL
Dynamic Positioning	DP 2 from Kongsberg
Accommodation	28 Persons
Bollard Pull	185.08mt
Deck Dimensions	540m <sup>2</sup> (37,5m x 14,4m)
Deck Load	900mt
Deck Strength	10mt/m <sup>2</sup>
Draft (max)	6.8m + 1.02m Skeg/Nozzle
Drill Water / WB	1231m <sup>3</sup> / 7743bbbls
Fuel Oil	1056m <sup>3</sup> / 6642bbbls
Deadweight	2350mt (d=6.8m)
Total BHP	15953 BHP
Towing/Working Winch Brake (Static/Band Brake)	550mt
Towing/Working Winch No 2 Brake (Static/Band Brake)	550mt
Secondary Winch Fibre Capacity - 203mm	1 x 1400m of 203mm
Chain Locker	4x101m <sup>3</sup> = 404m <sup>3</sup>
Gypsies	2 x 76mm, 2 x 84mm
Shark Jaws	2 x 750 MWL - Karm
Shark Jaws Insert	50mm - 125mm
Tow Pins	4 x 250 MWL - Karm
Smit Bracket	500mt MWL
Secondary Winch Number of Drums	1 Drums
Secondary Winch Brake	170mt

Secondary Winch Max Weight	100mt
Pot Water	741m <sup>3</sup> / 4661bbls
Pop Up Pins	2 x 90 MWL of Karm